

## AC VOLTAGE & METAL DETECTOR MS8902A/MS8902B

**MS8902A**

**VOLTAGE**  
AC 12V~600V

V MEM LED



**Features:**

- ▶ Pocket Size
- ▶ Non-Contact AC Voltage Detectors
- ▶ Sound and Light Instructions

EMC  
LVD



**Specifications**

MS8902A

MS8902B

Specifications	MS8902A	MS8902B
Non-Contact AC Voltage Detecting	●	●
AC Voltage Range	12V~600V AC/ 50~60Hz	20V~600V AC/50~500Hz
The Sensitivity of AC Voltage Adjusting and the Default Sensitivity of AC Voltage Setting	●	●
Metal Detecting		Detection Distance: <30mm
Sound and Light Instructions	●	●
Auto Power Off	●	●
Operating Temperature and Humidity	-10~50°C/ < 85%RH	-10~50°C/ < 85%RH
Double Molded Case	●	●
Low-Battery Indication	●	●
MEM Function (AC Voltage Sensitivity)	●	●
<b>General</b>		
Power Supply	2×1.5V AAA	1×12V A23S
Product Size	157×24×20mm/ 6.18"×0.94"×0.78"	157×24×20mm/ 6.18"×0.94"×0.78"
Product Weight	42g/0.091lb	45g/0.1lb
Safety Rating	CE ETL CAT.II 1000V CAT.III 600V RoHS	

**MS8902B**

**VOLTAGE**  
AC 20V~600V

V MEM LED

Apo

